



## PRO-FIT reducing bush PVC-U metric

### Model:

- Outlet: A and B = solvent cemented spigot in combination with reducing socket metric

| d    | d1   | d3   | PN    | d2   | Code        | SP | Weight | z    | z1   | z2   | L    |
|------|------|------|-------|------|-------------|----|--------|------|------|------|------|
| (mm) | (mm) | (mm) | (bar) | (mm) |             |    | (kg)   | (mm) | (mm) | (mm) | (mm) |
| 10   | 14   | 12   | 16    | 8    | 721 910 903 | 10 | 0.003  | 15   | 15   | 3    | 27   |
| 12   | 16   | 12   | 16    | 8    | 721 910 905 | 10 | 0.004  | 18   | 18   | 6    | 30   |
| 12   | 16   | 16   | 16    | 10   | 721 910 906 | 10 | 0.004  | 18   | 18   | 6    | 30   |
| 16   | 20   | 16   | 16    | 10   | 721 910 908 | 10 | 0.003  | 21   | 19   | 7    | 33   |
| 16   | 20   | 16   | 16    | 12   | 721 910 909 | 10 | 0.004  | 21   | 19   | 7    | 33   |
| 20   | 25   | 16   | 16    | 12   | 721 910 910 | 10 | 0.008  | 25   | 21   | 9    | 37   |
| 20   | 25   | 20   | 16    | 16   | 721 910 911 | 10 | 0.008  | 25   | 23   | 9    | 39   |
| 25   | 32   | 16   | 16    | 12   | 721 910 912 | 10 | 0.014  | 30   | 23   | 11   | 42   |
| 25   | 32   | 20   | 16    | 16   | 721 910 913 | 10 | 0.015  | 30   | 26   | 12   | 44   |
| 25   | 32   | 25   | 16    | 20   | 721 910 914 | 10 | 0.017  | 30   | 27   | 11   | 46   |
| 32   | 40   | 20   | 16    | 16   | 721 910 915 | 10 | 0.025  | 36   | 28   | 14   | 50   |
| 32   | 40   | 25   | 16    | 20   | 721 910 916 | 10 | 0.026  | 36   | 30   | 14   | 52   |
| 32   | 40   | 32   | 16    | 25   | 721 910 917 | 10 | 0.031  | 36   | 33   | 14   | 55   |
| 40   | 50   | 25   | 16    | 20   | 721 910 918 | 10 | 0.045  | 44   | 34   | 18   | 60   |
| 40   | 50   | 32   | 16    | 25   | 721 910 919 | 10 | 0.052  | 44   | 37   | 18   | 63   |
| 40   | 50   | 40   | 16    | 32   | 721 910 920 | 10 | 0.058  | 44   | 40   | 18   | 66   |
| 50   | 63   | 32   | 16    | 25   | 721 910 921 | 5  | 0.092  | 54   | 42   | 23   | 73   |
| 50   | 63   | 40   | 16    | 32   | 721 910 922 | 5  | 0.098  | 54   | 45   | 23   | 76   |
| 50   | 63   | 50   | 16    | 40   | 721 910 923 | 5  | 0.111  | 54   | 49   | 23   | 80   |
| 63   | 75   | 40   | 16    | 32   | 721 910 924 | 5  | 0.127  | 62   | 46   | 24   | 84   |
| 63   | 75   | 50   | 16    | 40   | 721 910 925 | 5  | 0.139  | 62   | 50   | 24   | 88   |
| 63   | 75   | 63   | 16    | 50   | 721 910 926 | 1  | 0.167  | 62   | 55   | 24   | 93   |
| 75   | 90   | 50   | 16    | 40   | 721 910 927 | 10 | 0.224  | 74   | 56   | 30   | 100  |
| 75   | 90   | 63   | 16    | 50   | 721 910 928 | 10 | 0.253  | 74   | 61   | 30   | 105  |
| 75   | 90   | 75   | 16    | 63   | 721 910 929 | 10 | 0.265  | 74   | 68   | 30   | 112  |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>