



Adaptor socket PVC-U metric Rp

Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Rp (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
12	1/4	16	721 910 204	10	0.010	4	27	22
16	3/8	16	721 910 205	10	0.016	5	31	27
20	1/2	16	721 910 206	10	0.025	5	36	32
25	3/4	16	721 910 207	10	0.032	5	40	36
32	1	16	721 910 208	10	0.057	5	45	46
40	1 1/4	16	721 910 209	10	0.087	5	51	55
50	1 1/2	16	721 910 210	10	0.126	7	59	65
63	2	16	721 910 211	5	0.206	7	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>