



Втулка редукционная, укороченная, PVC-C метрическая

Модель:

- С патрубками и раструбами для клеевого соединения

	d (mm)	d1 (mm)	PN (bar)	code	SP	weight (kg)	z (mm)	L (mm)
*	20	16	16	723 900 334	10	0,004	2	16
*	25	20	16	723 900 337	10	0,004	3	19
*	32	20	16	723 900 342	10	0,015	6	22
*	32	25	16	723 900 341	10	0,010	4	22
	40	20	16	723 900 348	10	0,023	10	26
	40	25	16	723 900 347	10	0,024	7	26
*	40	32	16	723 900 346	10	0,017	4	26
	50	20	16	723 900 355	10	0,036	15	31
	50	25	16	723 900 354	10	0,037	12	31
	50	32	16	723 900 353	10	0,050	9	31
*	50	40	16	723 900 352	10	0,032	5	31
	63	32	16	723 900 360	10	0,086	16	38
	63	40	16	723 900 359	10	0,074	12	38
*	63	50	16	723 900 358	10	0,061	6	38
	75	50	16	723 900 365	10	0,115	13	44
*	75	63	16	723 900 364	10	0,086	6	44
	90	50	16	723 900 372	10	0,196	20	51
	90	63	16	723 900 371	10	0,183	14	51
*	90	75	16	723 900 370	10	0,146	8	51
	110	63	16	723 900 378	5	0,329	24	61
*	110	90	16	723 900 376	5	0,283	10	61
	160	110	16	723 900 390	6	0,956	25	86
	225	160	16	723 900 396	2	2,380	33	119

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>